

Material: Acrylonitrile Butadiene Rubber (NBR) MAX SPARE Code: NT 90

Physical properties	Nominal	Units
Hardness	90-95	Shore A
ASTM D 2240, 23°C		
Tensile strength	> 102	Kg/cm ²
ASTM D 412, 23°C		
Elongation at break	> 100	%
ASTM D 412, 23°C		
Compression set	< 25	%
ASTM D 395, 100°C, 22 h, 25 %		
Air Ageing		
ASTM D 573, 100°C, 70 h		
Hardness Change	<(+15)	Points
Tensile Change	<(-20)	%
Elongation Change	<(-40)	%
Fluid Resistance, IRM-901		
ASTM D 471, 100°C, 70 h		
Hardness Change	-5 to+15	Points
Tensile Change	<(-25)	%
Elongation Change	<(-45)	%
Volume Change	-10 to +5	%
Fluid Resistance, IRM-903		
ASTM D 471, 100°C, 70 h		
Hardness Change	<(-15)	Points
Tensile Change	<(-45)	%
Elongation Change	<(-45)	%
Volume Change	0 to +35	%
Specific Gravity	1.29 ± 0.02	g/cc
ASTM D 792, 23°C		
Ash Content	<(10)	%
800°C, 2 Hrs		
Operating Temperature	-30 to 100	°C

Disclaimer